



Unisys Libra 400 Mainframe Configuration

1 - Libra 400 Rack 1 Quad Core System Includes:

Unisys FS1700-Identical Mainframe with a 2,430 Relative Performance Rating

ACC: ES3220 TOE SNP
ES3220 BCOM, TOE Enabled
TRG: PWR CRD NOT FI
KB: 105 USB KB US English
ACC: 1.44MB Floppy Drive
CBL: ES3220 Flex CBL FD
MEM: 4GBx1 667MHz DL RNK
Mouse: 2 Button Mouse / USB
PERC6i SAS RAID Controller, Int w/B
8 - 73GB 15K Disk 3.5" SAS
ES3220 48x IDE CD-RW/DVD ROM Drive, SAT
ES3220 TPM Motherboard ROW
ACC: ES3220 1000PT x 4 Intel
PWR Cord: IEC320-C13/C14
CTRL: SCSI 2CH U320
Display: 19" Black
ACC: 8 Socket Pwr. Strip 24/30A
1 - 4MM Tape Drive (DDS3-5)
Ethernet/Parallel Interface
1 - 45 PPM Laser Printer - Networked
Duplexing Module
32MB Memory
4MB Flash Memory
Dual Port 10/100 Ethernet

Miscellaneous

1 - MCP for Libra 400
17 - Dial-up Lines
1 - High Speed Internet and VPN Access (T1)
1 - FedLine Advantage Recovery Platform